

Table of Contents

VIEW	2
<i>Syntax</i>	2
<i>Example</i>	2

[Actions](#), [Action List](#), [UI](#), [Forms](#)

VIEW

This action is very similar to the EDIT action. The difference is that the process in which the action has been called does not wait for the user to change the values of the object and continues execution immediately after displaying the form. Also the VIEW action allows viewing the specific presentation of the business object.

Syntax

```
VIEW AttributeIdentifier() [ USING Id() or StringLiteral() ] [ NOEDIT ]
```

where AttributeIdentifier() must be the name of the business object.

Example

```
VIEW Account
```

Id() or StringLiteral optionally indicate presentation or form of the business object to be viewed, for example

```
VIEW Account USING 'Some fancy presentation'
```

where "Some fancy presentation" is the name of the presentation that must be configured with the Account object.

note

It is possible to optionally indicate the name of the specific section of the business object that will be displayed first, for example:

```
VIEW Account USING 'Form for administrators' FORM_SECTION 'Personal details'
```

note

If NOEDIT keyword is specified at the end of the action the form viewed will have all its input controls disabled, so that the user cannot change any of the values.

From:

<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:

http://www.awareim.com/dokuwiki/a_f/a/view?rev=1663092928

Last update: **2022/09/13 18:15**

