

Table of Contents

LIST	2
<i>Description</i>	2
<i>Parameters</i>	2
<i>Example</i>	2

[Index](#), [Function](#), [Function List](#), [Miscellaneous](#)

LIST

Description

Prints out a list of business objects as a table where each row represents a single list member. A list may be specified as an attribute or as a query string. Only specified attributes of each list member are printed out. This function is useful when it is necessary to print out a relatively small list inside a document or inside an e-mail (usually used inside a tag). Returns a table as a text string.

Parameters

1. Identifier of the list or a string identifying the query (either Rule Language string or the name of the existing query).
2. Delimiter to be used between attributes of a member.
3. Attribute names to be printed out. The name of the attribute to print out may be optionally followed by the print format (the name of the attribute and the format must be separated by comma). If format is not specified the default attribute format will be used.

Example

```
<<LIST(Client.Children, ' ', 'FirstName', 'LastName', 'Age,#')>>
```

```
<<LIST('FIND Child WHERE Child IN Client.Children', ' ',  
'FirstName', 'LastName', 'Age')>>
```

From:
<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:
http://www.awareim.com/dokuwiki/a_f/f/af/list

Last update: **2023/05/09 01:00**

