

Table of Contents

LIST_TABLE_START	2
<i>Description</i>	2
<i>Parameters</i>	2
<i>Example</i>	2

[Index](#), [Function](#), [Function List](#), [Reports And Documentation](#)

LIST_TABLE_START

Description

Whereas the [LIST_TABLE](#) function prints the entire table including the header, the combination of [LIST_TABLE_START](#) and [LIST_TABLE_END](#) functions allows using an existing header of the table. Just like the [LIST_TABLE](#) function it prints out members of a list of query results. However, you create the table in the document itself and only mark the start and end of the data. All tags in between the markers represent attributes to be printed (see example). AwareIM automatically inserts extra rows as required.

note

These functions can only be used inside tags in MS Word, Excel or HTML documents!

Parameters

[LIST_TABLE_START](#) function takes an identifier of the list or a string identifying the query (either Rule Language string or the name of the existing query)

see [LIST_TABLE](#) function. If the list identifier is used the second parameter may optionally indicate ordering of the list. [LIST_TABLE_END](#) has no parameters.

Example

```
Header1Header 2Header3
<<LIST_TABLE_START(Client.Children)>>
  <<Child.FirstName>> <<Child.LastName>>
  <<Child.Age>><<LIST_TABLE_END()>>
```

From:
<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:
http://www.awareim.com/dokuwiki/a_f/f/af/list_table_start

Last update: **2025/06/12 03:59**

