

Table of Contents

Integration With Other Systems 2

How To... 2

Integration With Other Systems

How To...

Use existing database tables

This is explained in detail in the [“Working with Data Stored in Existing Database Tables”](#) section.

Use data from several existing database tables

Sometimes you may want to connect to existing database tables but display data from several existing database table in a single query. With normal **AwareIM** objects you can do it using shortcuts. With existing database tables you can also define a “normal” **AwareIM** object that would have references to different objects stored in the existing database tables and then define shortcuts to different attributes in these objects.

A better approach, however, is to define a view in the existing database that would select data from different tables, and then create a special **AwareIM** object that would point to this view.

Integrate a credit card payment system

Many credit card payment systems, such as PayPal, require that your web site communicate with them via a particular URL. Whenever your web site needs to perform credit card payment the users need to click on the link with this URL, which will bring them to the web site of the credit card payment system. As part of the URL that your web site supplies to the credit card payment system you must also specify the URL that the credit card payment web site will use to return to your web site upon successful or un-successful completion of the payment.

If you want to integrate the credit card payment into your **AwareIM** system you need to configure the following:

1. Most credit card systems require that you pass certain parameters to the system as part of their URL, for example, PayPal system requires the following parameters (among others) - amount, currency_code, item_name etc. First of all you need to define a business object representing parameters of the payment with the attribute names being exactly equal to the names of the parameters you want to pass to the credit card payment system. For example, we could define PayPalPayment business object with amount, currency_code and item_name attributes.
2. Define an intelligent business object representing the credit card payment system, for example you can define the business object with the name PayPalSystem - see the [“Defining Intelligent Business Objects”](#) section for details.
3. Define the URL channel as the default channel for this business object - see the [“Setting Properties of URL Channel”](#) section. Specify the base URL of the credit card payment system as the “URL of the Service Provider” channel property. Specify the names of the parameters that the credit card payment system uses to identify the URL to return to as channel properties. For

example, PayPal system requires that the parameter names for the successful and unsuccessful completion of payment are `return` and `cancel_return` respectively. **AwareIM** will make sure that the values for these parameters are correctly set, so that the credit card system will return to the **AwareIM** system on successful or un-successful completion of the payment.

4. Define the payment service of this business object, for example `ProcessPayment` – see the “[Defining Services of Intelligent Business Object](#)” section for details. Specify the business object you created in step 1 as the service input. Select `Standard Reply` as the service reply.
5. Define a process that will initialize the instance of the business object representing parameters of the payment (for example, `PayPalPayment`) request the service using the [REQUEST SERVICE](#) action, for example:

```
CREATE PayPalPayment WITH PayPalPayment.amount=100, ...
REQUEST SERVICE ProcessPayment of PayPalSystem USING PayPalPayment
```

6. Define a menu item that will start the above process – see the “[Setting Menu Item Properties](#)” section. Alternatively you can set up a form operation to start the process – see the “[Adding/Editing Form Operations](#)” and “[Hyperlinks](#)”. When the process starts **AwareIM** will navigate to the web site of the payment system. After the payment has been completed the web site of the credit card payment system will return to the **AwareIM** system (**AwareIM** will automatically display whether the payment request has been fulfilled).

Expose a web-service - REST-ful or SOAP

AwareIM will automatically expose the services you configure for your system as web services, so that other software systems or web sites can use them – see the “[Adding/Editing Services](#)” section. **AwareIM** can expose a service either as SOAP or REST-ful web service (or both) All the details are explained in the “[Adding/Editing Services](#)” section.

Consume a web service - REST-ful or SOAP

To do this you need to define an intelligent business object by defining the REST communication channel with the object. This is described in the .

Register AwareIM application in Facebook

In order to allow users to login via Facebook you need to register your AwareIM application with Facebook. In order to do this:

- Go to the URL <https://developers.facebook.com/apps>
- Create a new application
- When specifying site URL for the application enter the following URL:

<http://YourServerName:8080/AwareIM>

You can use localhost instead of the server name when testing your application.

When specifying “redirect URI” of the application enter the following URI:

<http://YourServerName:8080/AwareIM/req.awfb2>

- Copy application id and secret that Facebook should assign to your application – you will need these when setting up login options (see [0910_login_fb_tw_ggl](#) sections)

When users login to your **AwareIM** application they should use the following URL:

<http://YourServerName:8080/AwareIM/logon.awfb?domain=YourBusinessSpaceName&testingMode=false>

Register AwareIM application in Twitter

In order to allow users to login via Twitter you need to register your AwareIM application with Twitter. In order to do this:

- Go to the URL <https://dev.twitter.com/apps>
- Create a new application
- When specifying callback URL for the application enter the following URL:

<http://YourServerName:8080/AwareIM>

You can use localhost instead of the server name when testing your application.

When specifying “redirect URI” of the application enter the following URI:

<http://YourServerName:8080/AwareIM/req.awtw2>

- Copy consumer key and secret that Twitter should assign to your application – you will need these when setting up login options (see [0910_login_fb_tw_ggl](#) section)

When users login to your AwareIM application they should use the following URL:

<http://YourServerName:8080/AwareIM/logon.awtw?domain=YourBusinessSpaceName&testingMode=false>

Register AwareIM application in Google

In order to allow users to login via Google you need to register your **AwareIM** application with Google. In order to do this:

- Go to the URL <https://code.google.com/apis/console>
- Create a new application
- When specifying redirect URI for the application enter the following URI:

<http://yourservername:8080/awareim/req.awggl2>

You can use localhost instead of the server name when testing your application.

When specifying “redirect URI” of the application enter the following URI:

<http://YourServerName:8080/AwareIM/req.awggl2>

- Copy client id and secret that Google should assign to your application – you will need these when setting up login options (see [0910_login_fb_tw_ggl](#) section)
- If using synchronization with the Google Calendar make sure that access to the calendar API is allowed!

When users login to your **AwareIM** application they should use the following URL:

<http://YourServerName:8080/AwareIM/logon.awggl?domain=YourBusinessSpaceName&testingMode=false>

From:
<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:
http://www.awareim.com/dokuwiki/docs/3400_how_to/0900_other_systems?rev=1783322676

Last update: **2026/07/06 07:24**

