

Table of Contents

Programmer's Reference Methods 2

[Manuals](#), [Programmers Reference](#), [Methods](#), [Front Page](#)

Programmer's Reference Methods

A

- [addNotification](#) (EntityIdentifier, INotification)
- [addReferences](#) (IProcess, String, Long, String, EntityIdAndName [])
- [addServiceRequest](#) (String, String, Object [])
- [afterColumnInit](#) (IReportEnvironment)
- [afterDetailEval](#) (IReportEnvironment)
- [afterGroupInit](#) (String, IReportEnvironment)
- [afterPageInit](#) (IReportEnvironment)
- [afterReportInit](#) (IReportEnvironment)

B

- [beforeColumnInit](#) (IReportEnvironment)
- [beforeDetailEval](#) (IReportEnvironment)
- [beforeGroupInit](#) (String, IReportEnvironment)
- [beforePageInit](#) (IReportEnvironment)
- [beforeReportInit](#) (IReportEnvironment)

C

- [calculate](#) (String, Object [], INodeHelper)
- [cancel](#) ()
- [canHaveExternalResources](#) ()
- [createDynamicTemplate](#) (String, String, byte [], String)
- [createEntity](#) (IProcess, String)

- `createEntityFromTemplate (IProcess, IEntityTemplate, ChangedReference [])`
- `createNotification (IProcess, String)`

D

- `deepCopy () / DataPresentationTemplate`
- `deepCopy () / IEntity`
- `deleteEntities (IProcess, EntityIdAndName [])`
- `deleteReferences (IProcess, String, Long, String, EntityIdAndName [])`

E

- `elementsRenamed (DataPresentationTemplate, RenamedElements, INodeChangeHelper, IDomainVersion)`
- `execute (IExecutionEngine, Object [])`
- `executeChildProcess (IProcess, String, IEntity [], Boolean)`
- `executeEntityService (IProcess, String, EntityIdentifier, IEntity [], String, Boolean)`
- `executeNamedQuery (IProcess, String, Integer, Integer)`
- `executeQuery (IProcess, Query, Integer, Integer)`
- `exportEntities (IProcess, IEntity [], String, ExportOptions)`

F

- `fillWithData (String, Map, IDocumentDataSource, DataPresentationTemplate, IDocEngineHelper, IDomainVersion, int, Boolean, int)`

G

- `getAccessLevel ()`

- `getAllReferences (IProcess, IEntity, String)`
- `getAttributePaths ()`
- `getAttributeValue (String)`
- `getAvailableFunctions ()`
- `getBinaryData (IProcess, String, Long, String)`

G cont.

- `getChannelSettingsEditor ()`
- `getChannelValues ()`
- `getClientEngine ()`
- `getDatabaseInterface ()`
- `getDefaultChannelSettings ()`
- `getDomainVersion ()`
- `getEditCommand ()`
- `getElementValue (String)`
- `getEntities (IProcess, EntityIdAndName [])`
- `getEntity (IProcess, String, Long)`
- `getExecutionContext (IProcess)`
- `getExpressionValue (String)`
- `getExpressionValueForCalculations (String)`
- `getExternalName ()`
- `getFramePanelId (frameName)`
- `getId ()`
- `getInputSourceClassName ()`
- `getIntelligenceTypeApplicability ()`
- `getLoadedResources ()`
- `getLoadedTemplate ()`
- `getLoginName ()`
- `getMainTabPanel ()`
- `getMessage ()`
- `getMessageValues ()`
- `getName () / IChannel`
- `getName () / IEntity`
- `getName () / IFunctionLibrary`
- `getNotification ()`
- `getObjectReferences (IProcess, IEntity, String)`
- `getOutputSinkClassName ()`
- `getPanelId (frameName, tabName,`

- contentPanelName)
- getProcessId ()
- getProgress ()
- getReferences (String)
- getRequiredFactPatterns (String, Collection)
- getServiceName ()
- getServiceParameters ()
- getServiceStatus ()

G cont.

- getSinkSettings ()
- getSourceSettings ()
- getStartupTime ()
- getSuspensionTime ()
- getTabPanelId (frameName, tabName)
- getTemplateFileType ()
- getTemplateType ()
- getTimeout ()
- getTypeClass (String, Collection)

H

- hasFunction (String, int)

I

- importData (IProcess, String, String, Integer, Boolean)
- importRelationships (IProcess, String, String, Integer)
- initialiseTemplate (DataPresentationTemplate, IDomainVersion)
- isRTL ()
- isServiceRequest ()
- isTestingMode ()

M

- MessageBuilder ()
- MessageInterpreter (DataObject [])
- multiUser ()

N

- next ()

P

- [printFile \(\)](#)
- [Programmer's Reference Methods](#)

R

- [reset \(\)](#)
- [resume \(IExecutionEngine, Object \[\]\)](#)

S

- [sendNotification \(IProcess, IEntity, INotification, String\)](#)
- [setAttributePaths \(String \[\] attributePaths\)](#)
- [setAttributeValue \(String, Object\)](#)
- [setBinaryData \(IProcess, String, Long, String, byte\[\]\)](#)
- [setElementValue \(String, Object\)](#)
- [setProgress \(int\)](#)
- [setReferences \(String, ObjectReference \[\]\)](#)
- [setTimeout \(long\)](#)
- [startEditing \(int, java.awt.Component, Properties, boolean\)](#)
- [supportsServiceDiscovery \(\)](#)

T

- [toSQL \(String, Collection, ISQLBuilderHelper\)](#)

U

- [updateEntity \(IProcess, IEntity, String \[\], Object \[\], ChangedReference \[\]\)](#)

V

- [validateSettings \(Properties, int\)](#)

From: <http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link: <http://www.awareim.com/dokuwiki/docs/3500/0900?rev=1680675440>

Last update: **2023/04/05 06:17**



