

## Table of Contents

addServiceRequest (String, String, Object []) ..... 2

[Index](#), [Programmers Reference](#), [Methods](#), [MessageBuilder Class](#), [AddServiceRequest](#)

## addServiceRequest (String, String, Object [])

```
public DataObject [] addServiceRequest (String componentName, String
serviceName, Object [] parameters)
```

This method constructs a message representing a service request

### Parameters

componentName	this should always be null
serviceName	the name of the service to call (the service with this name must be exposed by the service provider). If a message is sent to <b>AwareIM</b> the name of the service is the name of one of the methods exposed by the IExecutionEngineServices interface (see JavaDoc API)
parameters	the parameters of the service as an array of <a href="#">IEntity</a> objects or null if the service does not require any parameters. If a message is sent to <b>AwareIM</b> the parameters must correspond to the methods exposed by the IExecutionEngineServices interface (see JavaDoc API)

### Returns

An array of DataObjects representing the message that can be sent to **AwareIM**.

From:

<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:

[http://www.awareim.com/dokuwiki/pr\\_methods/addservicerequest](http://www.awareim.com/dokuwiki/pr_methods/addservicerequest)

Last update: **2025/06/12 04:00**

