

## Table of Contents

addServiceRequest (String, String, Object []) ..... 2

[Programmers Reference](#), [Methods](#), [MessageBuilder Class](#), [AddServiceRequest](#)

## addServiceRequest (String, String, Object [])

```
public DataObject [] addServiceRequest (String componentName, String
serviceName, Object [] parameters)
```

This method constructs a message representing a service request

### Parameters

|               |  |
|---------------|--|
| componentName | this should always be null   |
| serviceName   | the name of the service to call (the service with this name must be exposed by the service provider). If a message is sent to <b>Aware IM</b> the name of the service is the name of one of the methods exposed by the IExecutionEngineServices interface (see JavaDoc API)                    |
| parameters    | the parameters of the service as an array of <a href="#">IEntity</a> objects or null if the service does not require any parameters. If a message is sent to <b>Aware IM</b> the parameters must correspond to the methods exposed by the IExecutionEngineServices interface (see JavaDoc API) |

### Returns

An array of DataObjects representing the message that can be sent to **Aware IM**.

From:  
<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:  
[http://www.awareim.com/dokuwiki/pr\\_methods/addservicerequest?rev=1683076544](http://www.awareim.com/dokuwiki/pr_methods/addservicerequest?rev=1683076544)

Last update: **2023/05/03 01:15**

