

Table of Contents

executeEntityService (IPProcess, String, EntityIdentifier, IEntity [], String, Boolean) 2

[Programmers Reference](#), [Methods](#), [IExecutionEngine Interface](#), [IExecutionEngine Interface Methods](#), [ExecuteEntityService](#)

executeEntityService (IProcess, String, EntityIdentifier, IEntity [], String, Boolean)

```
public INotification executeEntityService (IProcessparent, String
serviceName, EntityIdentifier provider, IEntity [] parameters, String
channelTypeName, Boolean asynchronous)
throws ServerTimeoutException, AccessDeniedException, ExecutionException;
```

This method calls the specified service of the specified service provider.

Parameters

serviceName	the name of the service to call (the service provider must expose the service)
provider	the name and unique ID of the intelligent business object which provides the service
parameters	the instances of the business objects representing the service input if it is required or null if the service requires no input
channelTypeName	the name of the channel through which the service is requested. If null the service is requested through the default channel of the provider.
asynchronous	if true the service is called in a separate thread.

Returns

The notification appropriate to the reply type of the called service if the service call was successful.

From:

<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:

http://www.awareim.com/dokuwiki/pr_methods/executeentityservice?rev=1680587501

Last update: **2023/04/04 05:51**

