

Table of Contents

getExpressionValue (String) 2

[Programmers Reference](#), [Methods](#), [IDocumentDataSource Interface](#), [IDocumentDataSource Interface Methods](#), [getExpressionValue](#)

getExpressionValue (String)

```
public Object getExpressionValue (String expression)
throws Exception
```

This method calculates the value of an expression inside a tag. The expression may be a reference to the object's attribute (attribute path) or a more complicated arithmetic expression. If the expression contains the formatting expression, the result is converted to the specified format; otherwise it is converted to the format specified in the attribute (if a single attribute is used). The [fillWithData](#) method can use the `Object.toString ()` method to convert the result to `String` and put it in the output document instead of the tag.

Parameters

expression	the text of the expression. This is the text that is contained inside a tag (not including the tag symbols)
------------	---

Returns

The value of the expression - possible types of the Java object are presented in the table of the correspondence between attribute and Java types in the [Appendix A](#). `Null` can be returned if the value is undefined.

Throws

An exception if the value cannot be calculated for whatever reason.

From: <http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link: http://www.awareim.com/dokuwiki/pr_methods/getexpressionvalue?rev=1680669164

Last update: **2023/04/05 04:32**

