

# Table of Contents

resume (IExecutionEngine, Object []) ..... 2

[Programmers Reference](#), [Methods](#), [IProcess](#), [IProcess Methods](#), [Resume](#)

## resume (IExecutionEngine, Object [])

```
public Object resume(IExecutionEngine engine, Object reply)
throws SuspendProcessException, ExecutionException, AccessDeniedException;
```

This method is called by the **Aware IM** framework when the process receives the reply from the service provider and gets resumed.

### Parameters

engine	the call back interface that allows the process to call services of <b>Aware IM</b> . See <a href="#">IExecutionEngine</a> interface.
reply	reply received from the service provider. This is the instance of the <a href="#">INotification</a> object. The attributes of this notification can be used to check the specific values of the reply. For example, if a remote service of a service provider were called, the reply notification would have the attributes as defined by the service declaration exposed by the provider. If a process was resumed immediately after its suspension in order to commit the current transaction, the reply is null.

### Returns

should always return null.

### Throws

SuspendProcessException	if one of the methods of the <a href="#">IExecutionEngine</a> threw <a href="#">SuspendProcessException</a> or if a process wants to commit the current transaction.
ExecutionException	if something is wrong.
AccessDeniedException	shouldn't be thrown by the process component directly

- [getDatabaseInterface \(\)](#)
- [addNotification \(EntityIdentifier, INotification\)](#)
- [addReferences \(IProcess, String, Long, String, EntityIdAndName \[\]\)](#)
- [addServiceRequest \(String, String, Object \[\]\)](#)
- [afterColumnInit \(IReportEnvironment\)](#)
- [afterDetailEval \(IReportEnvironment\)](#)
- [afterGroupInit \(String, IReportEnvironment\)](#)
- [afterPageInit \(IReportEnvironment\)](#)
- [afterReportInit \(IReportEnvironment\)](#)
- [beforeColumnInit \(IReportEnvironment\)](#)
- [beforeDetailEval \(IReportEnvironment\)](#)
- [beforeGroupInit \(String, IReportEnvironment\)](#)
- [beforePageInit \(IReportEnvironment\)](#)
- [beforeReportInit \(IReportEnvironment\)](#)
- [calculate \(String, Object \[\], INodeHelper\)](#)
- [cancel \(\)](#)

- canHaveExternalResources ()
- createDynamicTemplate (String, String, byte [], String)
- createEntity (IProcess, String)
- createEntityFromTemplate (IProcess, IEntityTemplate, ChangedReference [])
- createNotification (IProcess, String)
- deepCopy () / IEntity
- deepCopy () / DataPresentationTemplate
- deleteEntities (IProcess, EntityIdAndName [])
- deleteReferences (IProcess, String, Long, String, EntityIdAndName [])
- elementsRenamed (DataPresentationTemplate, RenamedElements, INodeChangeHelper, IDomainVersion)
- execute (IExecutionEngine, Object [])
- executeChildProcess (IProcess, String, IEntity [], Boolean)
- executeEntityService (IProcess, String, EntityIdentifier, IEntity [], String, Boolean)
- executeNamedQuery (IProcess, String, Integer, Integer)
- executeQuery (IProcess, Query, Integer, Integer)
- exportEntities (IProcess, IEntity [], String, ExportOptions)
- fillWithData (String, Map, IDocumentDataSource, DataPresentationTemplate, IDocEngineHelper, IDomainVersion, int, Boolean, int)
- getAccessLevel ()
- getAllReferences (IProcess, IEntity, String)
- getAttributePaths ()
- getAttributeValue (String)
- getAvailableFunctions ()
- getBinaryData (IProcess, String, Long, String)
- getChannelSettingsEditor ()
- getChannelValues ()
- getClientEngine ()
- getDefaultChannelSettings ()
- getDomainVersion ()
- getEditCommand ()
- getElementValue (String)
- getEntities (IProcess, EntityIdAndName [])
- getEntity (IProcess, String, Long)
- getExecutionContext (IProcess)
- getExpressionValue (String)
- getExpressionValueForCalcs (String)
- getExternalName ()
- getFramePanelId (frameName)
- getId ()
- getInputSourceClassName ()
- getIntelligenceTypeApplicability ()
- getLoadedResources ()
- getLoadedTemplate ()
- getLoginName ()
- getMainTabPanel ()
- getMessage ()
- getMessageValues ()
- getName () / IEntity
- getName () / IChannel
- getName () / IFunctionLibrary

- `getNotification ()`
- `getObjectReferences (IProcess, IEntity, String)`
- `getOutputSinkClassName ()`
- `getPanelId (frameName, tabName, contentPanelName)`
- `getProcessId ()`
- `getProgress ()`
- `getReferences (String)`
- `getRequiredFactPatterns (String, Collection)`
- `getServiceName ()`
- `getServiceParameters ()`
- `getServiceStatus ()`
- `getSinkSettings ()`
- `getSourceSettings ()`
- `getStartupTime ()`
- `getSuspensionTime ()`
- `getTabPanelId (frameName, tabName)`
- `getTemplateFileType ()`
- `getTemplateType ()`
- `getTimeout ()`
- `getTypeClass (String, Collection)`
- `hasFunction (String, int)`
- `importData (IProcess, String, String, Integer, Boolean)`
- `importRelationships (IProcess, String, String, Integer)`
- `initialiseTemplate (DataPresentationTemplate, IDomainVersion)`
- `isRTL ()`
- `isServiceRequest ()`
- `isTestingMode ()`
- `MessageBuilder ()`
- `MessageInterpreter (DataObject [])`
- `multiUser ()`
- `next ()`
- `printFile ()`
- `reset ()`
- `resume (IExecutionEngine, Object [])`
- `sendNotification (IProcess, IEntity, INotification, String)`
- `setAttributePaths (String [] attributePaths)`
- `setAttributeValue (String, Object)`
- `setBinaryData (IProcess, String, Long, String, byte[])`
- `setElementValue (String, Object)`
- `setProgress (int)`
- `setReferences (String, ObjectReference [])`
- `setTimeout (long)`
- `startEditing (int, java.awt.Component, Properties, boolean)`
- `supportsServiceDiscovery ()`
- `toSQL (String, Collection, ISQLBuilderHelper)`
- `updateEntity (IProcess, IEntity, String [], Object [], ChangedReference [])`
- `validateSettings (Properties, int)`

From:

<http://www.awareim.com/dokuwiki/> - **Documentation**

Permanent link:

[http://www.awareim.com/dokuwiki/pr\\_methods/resume?rev=1680676032](http://www.awareim.com/dokuwiki/pr_methods/resume?rev=1680676032)

Last update: **2023/04/05 06:27**

